



172

PTO/SB/21 (09-06)

Approved for use through 03/31/2007. OMB 0651-0031

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

TRANSMITTAL FORM

(to be used for all correspondence after initial filing)

Total Number of Pages in This Submission

Application Number 10/710,969

Filing Date 08-15-2004

First Named Inventor JOBSON et al.

Art Unit 1724

Examiner Name GREENE, JASON M.

Attorney Docket Number 6730.058.PCUS00

ENCLOSURES (Check all that apply)

<input type="checkbox"/> Fee Transmittal Form	<input type="checkbox"/> Drawing(s)	<input type="checkbox"/> After Allowance Communication to TC
<input type="checkbox"/> Fee Attached	<input type="checkbox"/> Licensing-related Papers	<input type="checkbox"/> Appeal Communication to Board of Appeals and Interferences
<input type="checkbox"/> Amendment/Reply	<input type="checkbox"/> Petition	<input type="checkbox"/> Appeal Communication to TC (Appeal Notice, Brief, Reply Brief)
<input type="checkbox"/> After Final	<input type="checkbox"/> Petition to Convert to a Provisional Application	<input type="checkbox"/> Proprietary Information
<input type="checkbox"/> Affidavits/declaration(s)	<input type="checkbox"/> Power of Attorney, Revocation	<input type="checkbox"/> Status Letter
<input type="checkbox"/> Extension of Time Request	<input type="checkbox"/> Change of Correspondence Address	<input checked="" type="checkbox"/> Other Enclosure(s) (please identify below):
<input type="checkbox"/> Express Abandonment Request	<input type="checkbox"/> Terminal Disclaimer	- Postcard
<input type="checkbox"/> Information Disclosure Statement	<input type="checkbox"/> Request for Refund	
<input checked="" type="checkbox"/> Certified Copy of Priority Document(s)	<input type="checkbox"/> CD, Number of CD(s) _____	
<input type="checkbox"/> Reply to Missing Parts/Incomplete Application	<input type="checkbox"/> Landscape Table on CD	
<input type="checkbox"/> Reply to Missing Parts under 37 CFR 1.52 or 1.53		

Remarks

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT

Firm Name	NOVAK DRUCE & QUIGG, LLP		
Signature	/Tracy W. Druce/		
Printed name	Tracy W. Druce		
Date	03/23/2007	Reg. No.	35,493

CERTIFICATE OF TRANSMISSION/MAILING

I hereby certify that this correspondence is being facsimile transmitted to the USPTO or deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date shown below:

Signature			
Typed or printed name	Michelle Williams	Date	03/23/2007

This collection of information is required by 37 CFR 1.5. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to 2 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

PRV

PATENT- OCH REGISTRERINGSVERKET

Patentavdelningen

Intyg Certificate



Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.

This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.

(71) Sökande Volvo Technology Corp, Göteborg SE
Applicant (s) Ford Global Technologies Inc, Dearborn MI US

(21) Patentansökningsnummer 0200453-9
Patent application number

(86) Ingivningsdatum 2002-02-15
Date of filing

Stockholm, 2006-11-22

För Patent- och registreringsverket
For the Patent- and Registration Office

Ingegerd Karlsson
Ingegerd Karlsson

Avgift
Fee 170:-

Ink. t. Patent- och reg.verket

C14205, IF

2002-02-15

2002-02-14

Huvudfaxen Kassar

TITLE:

5 A device for treatment of a gas flow.

TECHNICAL FIELD:

The invention generally relates to a device for treatment of a gas flow. In particular, the invention relates to a device for catalytic purification of exhaust gases emanating from
10 internal combustion engines.

BACKGROUND ART:

Exhaust gases emanating from e.g. internal combustion engines or industrial processes generally contain potentially hazardous compounds such as hydrocarbons (HC), carbon
15 monoxide (CO), oxides of nitrogen (NO_x) and particulates. Such compounds need to be converted to harmless, or at least less hazardous, compounds in order to reduce the amount of hazardous compounds released to the environment. Commonly, the exhaust gases undergo some form of catalytic treatment and/or filtering process.

20 In most of the conversions of interest in this context, the temperature is an important feature. Many important conversion reactions require a rather high temperature. The use of catalysts, e.g. metals or metal oxides from the platinum group, makes it possible to convert the hazardous compounds with a satisfactory reaction rate at a much lower temperature than if catalysts are not used. However, a high reaction rate can only be achieved if the temperature
25 is sufficient, i.e. above the so called light-off temperature at which the catalyzed reaction rate becomes significant. The light-off temperature is usually in the range 200-400°C. If the light-off temperature has not yet been reached, or if the temperature falls below light-off so that the conversion stops, almost no hazardous compounds will be converted. These are well-known problems associated with e.g. cold start of an engine (with a similarly cold catalyzer) and with
30 "cold" exhaust gases, such as those emanating from a diesel engine.

The temperature is further important in regeneration of purification devices, e.g. the removal of trapped particles by combustion or the removal of impurities such as sulphur oxides (SO_x) from a catalytic device. Such processes can be cyclic and involve a temperature increase to

around 600°C for a certain time period. As the purification devices normally degrade if they are exposed to too high temperatures there is an upper temperature limit that should not be exceeded. Thus, it is not only the temperature that is an important feature, but also the control of the temperature; both at normal operation to achieve a good conversion and during
5 regeneration processes.

Another important feature is the pressure drop over the purification device as energy is needed to overcome the gas flow resistance of the device. For instance, an increased pressure drop over a purification device for a vehicle engine could result in an increased fuel
10 consumption.

A conventional physical structure of a catalytic converter, as for instance disclosed in US 3885977, is the ceramic honeycomb monolith with parallel, open channels. The catalytic material is deposited onto the walls of the honeycomb channels. As the gas flows from one
15 end to the other, the catalytic conversion takes place. This type of structure generally works well provided that the temperature of the device is above the light-off temperature. However, at cold-start situations it is difficult to avoid that hazardous compounds flow through the channels without conversion.

20 In order to reduce the amounts of hazardous compounds that are released during cold start it is a well known technique to use adsorption traps, i.e. to deposit a material, besides the catalysts, that adsorbs and retains cold hydrocarbons and/or nitrogen oxides until the catalyst reaches the light-off temperature. As an example, this is disclosed in WO95/18292. A problem with this technique when applied to the conventional physical structure described above is that the
25 desorption temperature for most compounds generally is lower than the temperature required for conversion. A great deal of the hazardous compounds will thus still flow through the channels without conversion.

Another approach to solve the problem with cold converters is to introduce electric heating, as disclosed in for instance WO92/14912. It is however difficult to make the heating fast enough and the costs for components and energy are high. This kind of electric heating may also be a safety risk (electricity, fire).

From the above, it is apparent that there is a need for improved gas treatment devices.

7602 -04- 1 5

Huvudföreläsningen

DISCLOSURE OF THE INVENTION:

The object of the present invention is to provide a device for treatment of a gasflow that makes it possible to achieve a higher efficiency in the conversion of the gas, compared to prior art. This objective is achieved by the technical features contained in claim 1. The following claims contain advantageous embodiments, further developments and variants of the invention.

A fundamental idea of this invention is the modular construction, i.e. the concept of joining a plurality of different sections together into one unit, and by this gain advantageous effects, both in the manufacturing process by an efficient production of the individual sections and other parts constituting the body, as well as in the performance of the assembled construction.

The invention concerns a device for treatment of a gas flow, comprising at least one body that is adapted to cause a conversion in the composition of the gas. The invention is characterized in that the body has a modular construction comprising a plurality of sections with different internal structures that allow gas to flow through the section, and that said sections are arranged so that at least a portion of the gas flows through at least two sections with different internal structures during operation of the device. In other words, the body is arranged so that the gas flows through different types of sections on its way through the body. In contrast to conventional constructions that consist of only one type of internal structure, the modular construction according to the invention makes it possible to combine advantageous properties of several different types of structures and to construct the body in many different ways. Further, the invention makes it possible to compose a body in such a way that certain technical main functions are assigned to certain sections that have been designed for the purpose, i.e. an individual section is designed in such a way that its technical properties are particularly well adapted for a certain function. For instance, a certain type of section may be excellent for conversion purposes but may suffer from a poor mechanical stability or a high flow resistance, or it may require a certain distribution of the gas flow to work properly. By combining such a section type with one or several other types of sections into one body, it is possible to overcome the drawbacks associated with the individual section types. Further, one type of section structure may be more favourable for conversion close to the inlet of the body, whereas another type of section structure may be more favourable for conversion close to the outlet of the body where the composition and in some cases also the temperature of the gas is

Huvudföreläggelsen

different. A body constructed according to the invention can thus be used to increase the conversion efficiency in a gas treatment device. The modular construction according to the invention is also advantageous in the waste management of a used gas treatment device as the sections can be taken care of individually after separation. For instance, one section may contain chemical elements such as catalyst material that are to be recovered, whereas another section may be dumped or re-used in another construction.

In a first advantageous embodiment of the invention, at least one of said sections exhibits a substantially unchanged cross section in at least one certain direction, preferably a plurality of said sections exhibit a substantially unchanged cross section in at least one certain direction. An advantageous effect of this feature is that the section(s) may be produced by extruding means which is a cost-effective production method that is well suited for both metal and ceramic material.

In a second advantageous embodiment of the invention, said sections are substantially made out of a ceramic material, preferably said sections are joined together by sintering, preferably the body is substantially made out of a ceramic material. This gives a favourable construction since a properly chosen ceramic material, compared to metal, has a lower cost of material, a lower cost of production, a lower thermal expansion, a better wash-coat adhesion and has a lower thermal mass per wall volume. A construction made out of a ceramic material is also less prone to degrade in the rough environment of an exhaust gas flow.

In a third advantageous embodiment of the invention, the body comprises at least one first section that is provided with a plurality of gas flow passages that extend essentially parallel to each other. Such a structure makes it possible to contact the gas with a large body surface which is advantageous in most types of gas treatment.

In a fourth advantageous embodiment of the invention, the body comprises at least one second section that also is provided with a plurality of gas flow passages that extend essentially parallel to each other, and the number of gas flow passages per cross section area unit differs between the first section and the second section. Thereby, it is possible to utilize the advantages of sections with a large number of passages per area unit, i.e. higher heat and mass transfer rates due to a shorter distance between the gas and the body surface (i.e. the wall that separates the passages), with the advantages of sections with a relatively small

2002-02-15

Huvudlexen Kesson

number of passages per area unit, i.e. a lower flow resistance and, usually, a higher mechanical stability. Preferably, said sections are arranged in such a way that at least a portion of the walls that define the gas flow passages in the first section form extensions of at least a portion of the walls that define the gas flow passages in the second section. Such an arrangement increases the mechanical stability of the construction and decreases the abrasion of the walls during operation, particularly in the case where the walls are sintered together.

In a fifth advantageous embodiment of the invention, the body is arranged to permit heat exchange between the gas flows in adjacent gas flow passages. This feature makes it possible to utilize the heat in the gas in a more efficient way which is an advantage under most operation conditions of a gas treatment device. A good heat economy is especially important if the incoming gas flow is relatively cold so that the temperature might fall below the catalyst light-off temperature described previously. Preferably, the device is arranged so that the main direction of the gas flow in one gas flow passage is essentially the opposite of the main direction of the gas flow in an adjacent gas flow passage during operation of the device. Thereby it is possible to achieve a counter-current heat exchange process for highest efficiency.

In a sixth advantageous embodiment of the invention, said gas flow passages form inlet passages that are intended for an incoming gas flow and outlet passages that are intended for an outgoing gas flow, and that a reversing zone is arranged in connection with said first section so that gas entering said reversing zone from the inlet passages is permitted to change direction and flow back through the outlet passages. Such an arrangement is simple and makes it possible to achieve a counter-current heat exchange process. Further, this arrangement makes it possible to, during cold start situations, adsorb compounds in or close to the reversing zone until the rest of the body has reached the catalyst light-off temperature.

In a seventh advantageous embodiment of the invention, the body comprises at least one second section that is provided with at least one first opening for the entrance of an incoming gas flow, and said second section is arranged in connection to at least one first section, and said second section is adapted to distribute the incoming gas flow to the said inlet passages. Preferably, said second section is provided with at least one second opening for the exit of an outgoing gas flow, and said second section is adapted to lead the outgoing gas flow out from said outlet passages. Such an arrangement gives an appropriate distribution of the gas flow

2002-02-15

Huvudföreläsning

and makes it possible to give the device a compact design. Additionally, it makes it possible to perform heat exchange also in the second section.

In an eighth advantageous embodiment of the invention, the second section comprises a wall structure forming at least one first channel to which the incoming gas flow is fed, and a plurality of second channels that extend from said first channel and which second channels are open to said inlet passages. This enables a simple construction and a good distribution of the incoming gas flow. Preferably, said first channel is closed to the gas flow passages. Thereby the incoming gas is forced to flow via the second channels which leads to a uniform distribution of the gas flow within the individual inlet passages. In a further improvement, the wall structure forms a plurality of third channels that are open to said outlet passages, preferably said third channels are formed between said second channels (30) using common walls. This is an advantageous way of leading the gas out as heat exchange can take place also in the second section, and as no additional walls are needed.

In a ninth advantageous embodiment of the invention, the second section comprises a zig-zag shaped wall structure forming a first and a second set of channels, one set on each side of said zig-zag shaped structure, wherein said first set of channels are open to said inlet passages and said second set of channels are open to said outlet passages, and wherein the incoming gas flow is fed to the first set of channels. Also this design enables a simple construction and a good distribution of the incoming gas flow, and makes it possible to perform heat exchange also in the second section.

In a tenth advantageous embodiment of the invention, said first section comprises an internal cavity that extends substantially parallel to said gas flow passages, and said gas flow passages are distributed around said internal cavity. Preferably, said second section comprises an internal cavity, and at least one first or second opening is directed towards said cavity so that gas flow via said cavity during operation of the device. Preferably, the body has a substantially cylindrical shape, preferably the body has a general shape of a circular cylinder, and that the body comprises an internal cavity that extends in the longitudinal direction of the body, and that the device is arranged in such a way that either incoming gas enters or outgoing gas exits the body via said internal cavity during operation of the device. Such a body can easily be composed using sections of the type previously described in this paragraph. An advantageous effect of this design is that the device require less space. A

15. FEB. 2002 15

Huvudlösen Kassan

further advantage, especially in a vehicle exhaust gas purification application, is that the device can be made with a long and narrow physical shape that can be arranged with its longitudinal axis in line with the exhaust pipe. By distributing the gas flow passages around the internal cavity and/or along the longitudinal axis of the body, this design enables a low pressure drop and advantageous packing properties.

In an eleventh advantageous embodiment of the invention, the body comprises at least one third section provided with walls that are permeable to the gas flow, said third section being primarily adapted to remove particulates from the gas. Thereby it is possible to use the device for filtering purposes, which is important in for instance the purification of exhaust gases emanating from a diesel engine. Preferably, the third section is arranged between the first section and the reversing chamber, and said permeable walls essentially defines an extension of the gas flow passages in the first section, and the outlet passages are closed to the reversing chamber so that the gas is forced to flow through said permeable walls during operation of the device. Such a design has several advantageous effects: the construction is relatively simple; ash and soot can accumulate in the reversing chamber instead of occupying useful filter volume; in combination with the heat exchange properties of the invention, the regeneration of the filter can be carried out very efficiently as the heat evolved in this process can be used for preheating purposes. Further, the third section may be produced by extruding means in similarity to the first and second sections.

BRIEF DESCRIPTION OF THE DRAWINGS:

The invention will now be described in more detail with reference to the following drawings where:

- 25 **Figure 1** shows, in a schematic perspective view, a first advantageous embodiment of the invention,
- Figure 2** shows, in an exploded perspective view, a second advantageous embodiment of the invention,
- Figure 3** shows a schematic sectional view of a variant of the second advantageous embodiment of the invention according to figure 2,
- Figure 4** shows a sectional view A-A according to figure 3,
- Figure 5** shows a sectional view B-B according to figure 3,
- Figure 6** shows a sectional view C-C according to figure 3
- Figure 7** shows a sectional view D-D according to figure 3,

112-15

Haraldsson Kassan

- Figure 8** shows a sectional view A-A according to figure 3 of an alternative variant of the second advantageous embodiment of the invention,
- Figure 9** shows a sectional view B-B according to figure 3 corresponding to the variant shown in figure 8, and
- Figure 10** shows a further development of the second embodiment of the invention according to figures 2 and 3.

DETAILED DESCRIPTION OF THE INVENTION:

Figure 1 shows, in a schematic view, a first advantageous embodiment of the invention. Two first sections 27 and two second sections 26 have been joined together as to form a body 3. Both the first sections 27 and the second sections 26 are provided with a plurality of gas flow passages 11 that extend essentially parallel to each other. The number of gas flow passages 11 per cross section area unit is four times higher in the second section 26 compared with the first section 27. A portion of the walls defining the gas flow passages 11 in the second section 26 thus form an extension of all the walls defining the gas flow passages 11 in the first section. A part of the body 3 has been removed in the figure to show the internal structure more clearly. During operation of the device the gas will flow through the body 3 as indicated by the arrows in the magnified part of the figure; gas entering the body 3 will thus experience low and high numbers of gas flow passages 11 per cross section area unit in an alternating manner. Preferably, the surfaces of the body 3 that comes into contact with the gas are coated with a catalyst material. Depending on the application, also an adsorption/desorption agent may be applied to said surfaces.

The number of flow passages (or channels) per cross section area unit is normally referred to as the channel density, which usually is expressed in cpsi (channels per square inch). In applications concerning vehicle exhaust gas purification, a typical value of the channel density is 400 cpsi, but channel densities of 600 and 900 cpsi have also been used in more recent applications. The sections in figure 1, which only shows a schematic view of the first embodiment of the invention, could thus for instance correspond to 200 cpsi (the first section 27) and 800 cpsi (the second section 26).

The general advantage of using a higher channel density is that the distance between the gas and the body surfaces (i.e. the walls that separates the channels/passages 11) becomes shorter which leads to higher heat and mass transfer rates. A high mass transfer rate is especially

2002-02-15

Fluorescence spectrum

important in high flow rate situations where it is important that an efficient conversion can be achieved in a small body volume. A high heat transfer rate is especially important to rapidly reach the light-off temperature, particularly in cases where the increased channel density leads to a decrease in total thermal mass of the body 3. An increased channel density makes it possible to make the channel walls thinner, but this does not necessarily lead to a decreasing thermal mass of the body 3 as the number of walls increase at the same time.

A general disadvantage of using a higher channel density is that the flow resistance increases, which only partly can be compensated for by decreasing the total volume of the body. The high flow resistance makes it necessary to give the body a more wide and short shape, i.e. if the channel density increases, the diameter of the body (perpendicular to the direction of the gas flow) needs to be increased and the length of the body (parallel to the direction of the gas flow) needs to be shortened. Such a body shape suffer from a low mechanical stability, especially if the walls are made thinner.

By composing a body 3 as schematically shown in figure 1 it is possible combine the advantageous properties of low and high cell densities. The second sections 26 are provided with a large number of gas flow passages 11 per cross section area unit and they therefore contribute with a high mass and heat transfer for efficient conversion and rapid light-off. The first sections 27 are provided with a relatively low number of gas flow passages 11 per cross section area unit and contribute to the conversion of gas, but contribute also with mechanical stability. By combining said first 27 and second 26 sections in an alternating manner it is possible to utilize the advantageous of a high cell density and at the same time keep the flow resistance at a reasonably low level and give the body 3 a relatively long and narrow shape for high mechanical stability.

As shown in figure 1, the walls that define the gas flow passages 11 in the second section 26 are made thinner than the walls of the first section 27, in order to further shorten the time to reach the light-off temperature. By joining the sections together, the walls in the second sections 26 can be made very thin as the first sections 27 stabilize the construction. This is especially true if the sections, including the walls, are made in a ceramic material and are sintered together. The relatively thick walls in the first section 27 are useful for heat storage. However, the advantageous effects of the invention can be utilized even if the walls in the different sections are of the same thickness.

Ink. t. Patent- och reg. Market

2002-02-15

Husvaller och Kesson

As seen from figure 1, the sections exhibit a substantially unchanged cross section in the direction corresponding to the main direction of the gas flow (downwards through the paper). It is thus possible to produce the individual sections by extruding means which is suitable for both metal and ceramic material, and to join them together after the extruding process. Metallic sections are preferably joined by soldering, whereas ceramic sections are preferably sintered together. The advantages of using a ceramic material is described previously.

A second advantageous embodiment of the invention is shown in figures 2 to 9. In this embodiment the body is arranged to perform heat exchange between gas flows in adjacent gas flow passages. Figure 2 shows, in an exploded perspective view, the structure of a body 3 comprising one second section 26, two first sections 27 and two reversing sections that comprise reversing zones in the form of reversing chambers 13. Each first section 27 is provided with a plurality of gas flow passages 11 and, compared with the thin walls defining the gas flow passages 11, relatively thick supporting walls 33 that divides the first section 27 into a number of sectors. The body 3 has the shape of a circular cylinder and comprises an internal cavity 20 that extends in the longitudinal direction of the body. The incoming gas flow is fed into the body 3 via the internal cavity 20 and the outgoing gas flow leaves the body 3 via its periphery. These flow processes are further described below. The internal structures, and thereby the technical properties, differ between the different sections in that i) the first section 27 is primarily adapted to cause a conversion in the composition of the gas and to permit a heat exchange process, ii) in that the second section 26 is primarily adapted to distribute the gas in to and out from the first section 27, iii) and in that the reversing section is primarily adapted to form a counter-current flow system by allowing the gas to change direction and flow back via another flow passage.

Figure 3 shows a schematic sectional view of a variant of the second embodiment wherein the body 3 constitutes two sub-bodies that have been joined together, and wherein each sub-body has a structure according to figure 2. The body 3 has also been provided with surrounding equipment for leading the gas to and from the body 3. Figures 4, 5, 6 and 7 show sectional views A-A, B-B, C-C and D-D, respectively, according to figure 3. The structure of the second section 26 is not shown in figure 3, but in figure 4.

702-02-15

Huvudföreläggaren Kassan

The incoming gas flow is fed into the body 3 through the entrance opening 4 into the internal cavity 20. The other end 23 of said cavity 20, opposite to that of the entrance opening 4, is closed which has the effect that the incoming gas flow is forced through the first openings 4' of each second section 26. As can be seen in figure 4, the second section 26 constitutes of a wall structure forming (as an example) four first channels 29 that communicate with the internal cavity 20 via the first openings 4' and to which first channels 29 the incoming gas flow is fed. The wall structure further forms a plurality of second channels 30 (in the figure there are, as an example, five in each direction) that extend from each of said first channels 29. As can be seen in figure 5, the first section 27 is provided with a plurality of gas flow passages 11a, 11b. Every second of these passages forms an inlet passage 11a intended for an incoming gas flow, and every second passage forms an outlet passage 11b, intended for an outgoing gas flow. Said second channels 30 (fig. 4) are open to the gas flow inlet passages 11a, whereas said first channels 29 are closed to all gas flow passages 11a, 11b by the ends of the supporting walls 33. In order to make it possible to use thinner supporting walls 33 and thereby decrease the amount of construction material in the body, the direct passage from the first channels 29 to the gas flow passages 11a, 11b can be closed by blocking means, for instance thin plates, or by plugging appropriate parts of the passages. As the incoming gas flow is fed through the first openings 4' into the first channels 29, the gas is forced to be distributed into the second channels 30. From the second channels 30, the gas flow is fed to the inlet passages 11a. Further, the gas flows through the inlet passages 11a and enters the reversing chamber 13 allowing the gas flow to change direction and flow back to the second section 26 via the outlet passages 11b. The wall structure forming the first channels 29 and the second channels 30 in the second section 26 also forms a plurality of third channels 32 (in the figure there are, as an example, five in each direction) between said second channels 30 using common walls. Said third channels 32 are open to the gas flow outlet passages 11b. Two sets of said third channels 32 emerge into a common fourth channel 34. In figure 4 it can be seen that the second section 26, as an example, is provided with four fourth channels 34. The outgoing gas flow enters said third channels 32 from the outlet passages 11b and exits the second section 26 via said fourth channels 34 and a second opening 5' into an outlet channel 35 in the periphery of the body 3. At the end of the body 3, opposite to that of the entrance opening 4, the outlet channels 35 are combined to a common exit opening 5 for the exit of the outgoing gas flow from the body 3.

1. 12. 2001 15

Huvudförfaren Kärsson

Figure 6 shows a sectional view of the section comprising the reversing chamber 13. As a variant, the reversing chamber 13 could be divided up into a number of sectors. Figure 6 also shows the internal cavity 20 and the outlet channels 35. Figure 7 shows a sectional view of a delimiting plate 24 located between the two sub-bodies. Such plates 24 can be used to stabilize the construction. As an alternative to what is shown in figure 3, the delimiting plate 24 may form the end part of the reversing chambers 13 of two adjacent sub-bodies.

In order to lead the gas to the body 3, a pipe (for instance an exhaust pipe) is preferably inserted through the entrance opening 4 all the way to the other end 23 of the internal cavity 20. By providing the pipe with openings around its circumference at a location corresponding to the location of the second section(s) 26, the gas is permitted to flow into the second section(s) via the first openings 4'. A pipe provided with openings can also be inserted through the exit opening 5 in order to lead the gas away from the body 3. Such inserted pipes can be used to stabilize the construction.

Figures 8 and 9 show an alternative variant of the second embodiment of the invention. The principal of this variant is similar, but the first and the second section has a different internal shape. Figure 8 shows a sectional view A-A according to figure 3 of the alternative second section 26', and figure 9 shows a sectional view B-B according to figure 3 of the alternative first section 27'. Referring to figure 8, the second section 26' comprises a zig-zag shaped wall structure forming a first set of channels 40 and a second set of channels 41, one set on each side of said zig-zag shaped structure. The first set of channels 40 are, via the first openings 4', open to the internal cavity 20 and to the gas flow passages that are intended for an incoming gas flow: the inlet passages 11a. The second set of channels 41 are open to the gas flow passages that are intended for an outgoing gas flow: the outlet passages 11b, and to the outlet channels 35. The appearance of the gas flow passages 11a, 11b is shown in figure 9, wherein every second passage forms an inlet passage 11a and every second passage forms an outlet passage 11b in similarity to what is mentioned previously. In this variant of the invention, the gas flows in a similar way as described above; it enters the internal cavity 20 via the entrance opening 4, enters the first set of channels 40 via the first openings 4', flows through the inlet channels 11a to the reversing chamber 13 where it changes direction and flows through the outlet channels 11b to the second set of channels 41, and passes the second openings 5' into the outlet channels 35.

15. FEB 2002 13:17

Hövelin, Johan, Kåssan

An advantage of using more than one sub-body, as exemplified in figure 3, is that the incoming gas flow can be divided into several smaller gas flows which increases the efficiency of the device and lowers the pressure drop over the construction. Of course, more than two sub-bodies can be arranged together. Other arrangements are also possible, one example is to arrange only one first section 27 adjacent to the second section 26, and thus to block the other side of the second section 26. This arrangement may be used to achieve a higher mechanical stability of the construction. Another alternative is to reverse the direction of the gas flow so that the gas enters the body 3 via the outlet channels 35 and exits the body 3 through the opening 4.

As seen from figures 2 to 9, both the the first section 27, 27' and the second section 26, 26' exhibit a substantially unchanged cross section in the longitudinal direction of the body. This means that these sections may be produced by extruding means which is a cost-effective production method that is suitable both for metal and ceramic material. Preferably, all sections/parts of the construction are made out of a ceramic material and joined to each other by sintering means. This gives a durable construction. To achieve a heat exchange effect between the inlet and outlet passages, the walls separating the passages must be reasonably thin. For a ceramic material a wall thickness of about 0.1 mm would give a fast heat transfer through the wall compared to the heat transfer from the gas to the wall. An example of a suitable ceramic material is cordierite.

A further development of the second embodiment of the invention (figs. 2 and 3) is the adaption of the device to remove particulates in the gas. Figure 10 shows schematically the principles of a third section 36 arranged between a first section 27 and the section forming the reversing chamber 13. Although the design of the reversing chamber 13 may be similar to the above descriptions, it has in this case a different function as will be described below. Both the first section 27 and the third section 36 are provided with gas flow inlet and outlet passages 11a, 11b as described above. Plugs 37 close the outlet passages 11b to the reversing chamber 13. The walls 39 between the passages 11a, 11b in the third section 36 are permeable to the gas flow and exhibit preferably a porous structure through which gas can pass but not particles (larger than a certain size), which particles at least partly will be deposited in the reversing chamber 13. These gas flow permeable walls 39 thus work as filters. Due to the plugs 37, a pressure builds up in the reversing chamber 13. The gas flow in the inlet passages 11a is thus forced through the walls 39 in the third section 36 into the outlet passages 11b

Hörsal: Hörsal Kassel

back to the first section 27, as indicated by arrows in figure 10. Principally, the filtering process could be carried out in the first section 27, but permeable walls in this section would decrease the heat exchange properties. After some time, the filtering walls 39 and the reversing chamber 13 need to be regenerated by combustion of the soot. Due to the heat exchange properties of the second embodiment of the invention, the heat evolved in this process can be utilized efficiently in that the outgoing gas preheats the incoming gas in the first section 27. As an aid in this process, a heating coil can be placed in the reversing chamber 13. In conventional ceramic particle filters, the ash produced in the soot combustion process accumulates in the filtering channels occupying useful filter volume. According to figure 10, the ash 38 can instead at least partly be accumulated in the reversing chamber 13. In some applications, the volume of the reversing chamber 13 is sufficient for accumulating ash 38 during the service life of the gas treatment device. In other cases it is possible to provide the reversing chamber 13 with emptying means, such as an opening that is closed under normal operation.

The third section 36 shown in figure 10 is easily adapted to fit between the first section 27 and the section forming the reversing chamber 13 shown in figures 2 and 3. Further, the principal shape of the third section 36 is the same as that of the first section 27; the internal structures differ essentially in that the walls 39 in the third section are permeable to the gas flow. Thus, also the third section 36 exhibits a substantially unchanged cross section in a certain direction and may therefore be produced by extruding means, be made out of a ceramic material, and joined by sintering to other ceramic sections. The plugs 37 can be arranged by conventional means during or after the extrudation process. Of course, the third section 36 can be adapted to be used together with the alternative first section 27' shown in figure 9.

Although the use of the ash-accumulating reversing chamber 13 is advantageous, it is also possible to use the third section 36 without the reversing chamber 13 e.g. by plugging also the inlet passages 11a or by substituting the reversing chamber 13 for a delimiting plate 24.

An advantage of using a counter-current heat exchange in the treatment of a gas flow according to the second embodiment of the invention is that the heat can be utilized very efficiently. Besides the amount of heat contained in the incoming gas, heat may be supplied to the gas from exothermic reactions in the body, preferably by using a catalyst material that has been coated onto at least a part of the surfaces in the body that are in contact with the gas

10-7-02-15

Hervé/Joan Kesson

- flow. Heat may also be supplied by an external source such as a heat generator preferably arranged in the reversing zone. As the outgoing gas flow during its transport from the reversing chamber 13 to the second opening 5' can transfer a great deal of its heat to the incoming gas flow from the first opening 4' to the reversing chamber 13, only a small part of the supplied heat will leave the body 3 with the outgoing gas flow and thus be wasted. A good heat economy is especially important if the incoming gas flow is relatively cold so that the temperature might fall below the catalyst light-off temperature described previously. An example of this is when the device is applied to purify the exhaust gases of a diesel engine.
- 10 The heat exchange process according to the second embodiment of the invention is also very useful in temperature transient situations, such as the purification of exhaust gases during a cold start situation. In such an application of the invention, the body 3 is preferably provided with both a catalyst material and an adsorption/desorption agent applied to at least a part of the surfaces in the body 3 that are in contact with the gas flow. Said agent preferably adsorbs
- 15 hydrocarbons and/or nitrogen oxides at, or below, a first temperature and releases them at, or above, a second temperature which is higher than the first temperature. As the exhaust gases enters the cold body 3, heat will be transferred from the gas to the material comprised in the body 3. The first part of the heat exchanger surfaces, i.e. the material in or close to the second section 26 located closest to the first opening 4', heats up quickly while the part close to the reversing chamber 13 heats up slowly. As the body is arranged to permit heat exchange
- 20 between adjacent passages, also the heat exchanger surfaces closest to the second opening 5' will heat up quickly. A gas flow passing the device shortly after start up will thus experience a first hot zone at the entrance of the body 3, a zone with gradually decreasing temperature (the inlet passages 11a), a zone with gradually increasing temperature (the outlet passages 11b), and a second hot zone before exit out of the body 3. Compounds adsorbed onto
- 25 adsorption/desorption agents applied to surfaces in the first hot zone will relatively quickly desorb, but will be adsorbed again onto agents applied to colder surfaces close to the reversing chamber 13. As the temperature with time also increases close to the reversing chamber 13, the compounds will again desorb. This time, however, the compounds will be transported towards zones with higher temperatures. By properly designing the body and choosing catalyst material and adsorption/desorption agents, the temperature in at least the hottest zone will be above the catalyst light-off temperature so that the compounds are converted efficiently.
- 30

15

Håvard Johnsson

In order to improve the heat economy and to reduce the amounts of adsorption/desorption agents and catalysts required, one may carefully choose the body surfaces to which catalysts and agents should be applied. For instance, catalysts for oxidizing HC and CO and reducing NO_x may chiefly be applied in the hotter zones of the body (in or close to the second section 26), and adsorption/desorption agents may chiefly be applied in the colder zones (in or close to the reversing chamber 13).

In order to control the temperature of the gas flow in the body, the device preferably comprises one or several of the following: a heat generator arranged in the body (preferably arranged in the reversing chamber), cooling flanges arranged in the body, arrangements for introducing cooling air into the body, and/or a system for controlling the composition of the incoming gas flow. Said system preferably comprises an arrangement for introduction of oxidizing species, such as air, into the incoming gas flow, and/or an arrangement for introduction of oxidizable species, such as hydrocarbons, into the incoming gas flow. Due to the heat exchange properties of the device, the heat generated in the induced chemical reactions can effectively be taken care of.

If the device is arranged in connection to an engine, said system for controlling the composition of the incoming gas flow preferably comprises an arrangement for controlling the operation of the engine, which operation in turn can affect the composition of the incoming gas flow. For instance, by mixing additional amounts of fuel in one or several of the cylinders one may introduce fuel, i.e. hydrocarbons, into the exhaust gas that is to be purified in the gas treatment device.

The second embodiment of the invention is not limited to the above description. For instance, the reversing zone may be designed in different ways. One example is to substitute the reversing chamber 13 for transfer passages, e.g. holes, between the gas flow inlet and outlet passages. In the case of the further development of the second embodiment of the invention shown in figure 10, the reversing zone is arranged by using permeable walls 39. Further, it is possible to use a conventional monolith with a large number of narrow flow passages (and provided with the internal cavity 20) as an alternative to the first sections 27, 27' shown in figures 5 and 9. Each of the gas flow passages in figures 5 or 9 would in such a case be substituted for a number of more narrow passages side by side. With a proper design, this arrangement would give a more stable construction and only have a slight effect on the heat

1 5

However, it would increase the pressure drop and require more material.

exchange (due to the additional body content of material required for the additional walls).

However, it would increase the pressure drop and require more material.

The invention is not limited to the above described embodiments, but a number of

5 modifications are possible within the frame of the claims.

For instance, the body 3 may be composed of many more first 27 and second sections 26, and the body may also comprise other types of sections with other structures.

10 It is not necessary that the sections are joined together directly, they might also be joined indirectly via a part situated in between the sections.



Ink. t. Patent - eskimotat

2002-02-15

CLAIMS:

Huvudbeteckningen

1. A device for treatment of a gas flow, comprising at least one body (3) that is adapted to cause a conversion in the composition of the gas,

characterized in

that the body (3) has a modular construction comprising a plurality of sections (26, 26', 27, 27', 36) with different internal structures that allow gas to flow through the section, and that said sections (26, 26', 27, 27', 36) are arranged so that at least a portion of the gas flows through at least two sections with different internal structures during operation of the device.

2. A device according to anyone of claim 1,

characterized in

that at least one of said sections (26, 26', 27, 27', 36) exhibits a substantially unchanged cross section in at least one certain direction, preferably a plurality of said sections (26, 26', 27, 27', 36) exhibit a substantially unchanged cross section in at least one certain direction.

3. A device according to claim 1 or 2,

characterized in

that said sections (26, 26', 27, 27', 36) substantially are made out of a ceramic material, preferably said sections (26, 26', 27, 27', 36) are joined together by sintering, preferably the body (3) is substantially made out of a ceramic material.

4. A device according to anyone of the preceding claims,

characterized in

that the body (3) comprises at least one first section (27) that is provided with a plurality of gas flow passages (11) that extend essentially parallel to each other.

5. A device according to claim 4,

characterized in

that the body (3) comprises at least one second section (26) that also is provided with a plurality of gas flow passages (11) that extend essentially parallel to each other, and that the number of gas flow passages (11) per cross section area unit differs between the first section (27) and the second section (26).

Ink. t. Patent- och registeret

2002-02-15

Brevetföretag Kåron

6. A device according to claim 5,
characterized in

that the first and the second sections (26, 27) are arranged in such a way that at least a portion
of the walls that define the gas flow passages (11) in the first section (27) form extensions of
at least a portion of the walls that define the gas flow passages (11) in the second section (26).

7. A device according to claim 4,
characterized in

that the body (3) is arranged to permit heat exchange between gas flows in adjacent gas flow
passages (11).

8. A device according to claim 7,
characterized in

that the device is arranged so that the main direction of the gas flow in one gas flow passage
(11) is essentially the opposite of the main direction of the gas flow in an adjacent gas flow
passage (11) during operation of the device.

9. A device according to claim 7 or 8,
characterized in

that said gas flow passages (11) form inlet passages (11a) that are intended for an incoming
gas flow and outlet passages (11b) that are intended for an outgoing gas flow, and that a
reversing zone (13) is arranged in connection with said first section (27) so that gas entering
said reversing zone (13) from the inlet passages (11a) is permitted to change direction and
flow back through the outlet passages (11b).

10. A device according to claim 9,
characterized in

that said reversing zone (13) comprises a reversing chamber (13).

11. A device according to claim 9 or 10,
characterized in

that the body (3) comprises at least one second section (26, 26') that is provided with at least
one first opening (4') for the entrance of an incoming gas flow, and that said second section

1 2 3 4 5

Hovedlinjen i Hovedlinjen

(26, 26') is arranged in connection to at least one first section (27, 27'), and that said second section (26, 26') is adapted to distribute the incoming gas flow to the said inlet passages (11a).

12. A device according to claim 11,

characterized in

that said second section (26, 26') is provided with at least one second opening (5') for the exit of an outgoing gas flow, and that said second section (26, 26') is adapted to lead the outgoing gas flow out from said outlet passages (11b).

13. A device according to claim 11 or 12,

characterized in

that the second section (26) comprises a wall structure forming:

at least one first channel (29) to which the incoming gas flow is fed;

and a plurality of second channels (30) that extend from said first channel (29) and which

second channels (30) are open to said inlet passages (11a).

14. A device according to claim 13,

characterized in

that said first channel (29) is closed to the gas flow passages (11a, 11b).

15. A device according to claim 12 and 13 or 14,

characterized in

that the wall structure forms a plurality of third channels (32) that are open to said outlet passages (11b), preferably said third channels (32) are formed between said second channels

(30) using common walls.

16. A device according to claim 12,

characterized in

that the second section (26') comprises a zig-zag shaped wall structure forming a first and a second set of channels (40, 41), one set on each side of said zig-zag shaped structure, wherein said first set of channels (40) are open to said inlet passages (11a) and said second set of channels (41) are open to said outlet passages (11b), and wherein the incoming gas flow is fed to the first set of channels (40).

Ink t. Patent och register

1 27-14-1 5

Huvudföretag: Kertan

17. A device according to anyone of claims 9 to 16,

characterized in

that said first section (27, 27') comprises an internal cavity (20) that extends substantially parallel to said gas flow passages (11a, 11b), and that said gas flow passages (11a, 11b) are distributed around said internal cavity (20).

18. A device according to anyone of claims 11 to 17,

characterized in

that said second section (26, 26') comprises an internal cavity (20), and that at least one first or second opening (4', 5') is directed towards said cavity (20) so that gas flow via said cavity (20) during operation of the device.

19. A device according to anyone of claims 7 to 18,

characterized in

that the body (3) has a substantially cylindrical shape, preferably the body (3) has a general shape of a circular cylinder, and that the body (3) comprises an internal cavity (20) that extends in the longitudinal direction of the body (20), and that the device is arranged in such a way that either incoming gas enters or outgoing gas exits the body (3) via said internal cavity (20) during operation of the device.

20. A device according to anyone of claims 9 to 19,

characterized in

that the body (3) comprises at least one third section (36) provided with walls (39) that are permeable to the gas flow, said third section (36) being primarily adapted to remove particulates from the gas.

21. A device according to claim 20,

characterized in

that the third section (36) is arranged between the first section (27, 27') and the reversing chamber (13), and that said permeable walls (39) essentially defines an extension of the gas flow passages (11a, 11b) in the first section, and that the outlet passages (11b) are closed to the reversing chamber (13) so that the gas is forced to flow through said permeable walls (39) during operation of the device.

VTD PATENT +46 31 820040

NR. 6120 S. 26

VTD PATENT +46 31 820040

22. A device according to any of the preceding claims,
characterized in

that at least a part of the surfaces in the body (3) that are in contact with the gas flow are coated with a catalyst material.

5

23. A device according to any of the preceding claims,
characterized in

that at least a part of the surfaces in the body (3) that are in contact with the gas flow are coated with an adsorption/desorption agent.

10

24. A device according to any of the preceding claims,
characterized in

that the device comprises means for controlling the temperature of the gas flow in the body (3), said means comprising one or several of the following:

15

- a heat generator arranged in, or in connection to, the body (3)
- cooling flanges arranged in, or in connection to, the body (3)
- arrangements for introducing cooling air into the body (3)
- a system for controlling the composition of the incoming gas flow.

20

25. A device according to claim 24,
characterized in

that said system for controlling the composition of the incoming gas flow comprises one or both of the following:

25

- an arrangement for introduction of oxidizing species, such as air, into the incoming gas flow
- an arrangement for introduction of oxidizable species, such as hydrocarbons, into the incoming gas flow.

30

26. A device according to claim 24,
characterized in

that the device is arranged in connection to a combustion engine, and that said system for controlling the composition of the incoming gas flow comprises an arrangement for controlling the operation of the combustion engine, which operation in turn affects the composition of the incoming gas flow.

Intern. Patent- och registrat

15-02-15

Hans-Kristian Kjus

27. A device according to any of the preceding claims,**characterized in****that the device is adapted to purify the exhaust gas from an internal combustion engine,**
preferably in a mobile application.

Ink. i P. 101 och reg. verkst
1/12-02 1 5
Hoyad, Lenn Kesson

1/7




Fig.1

Inventor: Kasper J. Jørgensen

Attorney: J. J. Jensen

Filed: 15. Feb. 2002

2/7






Fig. 2

417




Ink. t. Patent och Företagsregister

2002-02-15


Meddelande

5/7



D-D

Fig. 7



C-C

Fig. 6

000045303

Invent. Patent- och registreringsverket

002-02-15

Hans-Joachim Krosch

7/7




Fig.10

ABSTRACT:

The invention concerns a device for treatment of a gas flow, comprising at least one body 3 that is adapted to cause a conversion in the composition of the gas. The invention is characterized in that the body (3) has a modular construction comprising a plurality of sections (26, 26', 27, 27', 36) with different internal structures that allow gas to flow through the section, and that said sections (26, 26', 27, 27', 36) are arranged so that at least a portion of the gas flows through at least two sections with different internal structures during operation of the device.

10 (Figure 2)

2002-02-15